

型号	主要尺寸				额定载荷		最大转速		重量
Bearing No.	Main Dimension(mm)				Load Rating(KN)		Max Runout Speed		Weight
	Bore	Outer Diamete	Width	Radius(r)	Dynamic	Static	Grease	Oil	
	内径	外径	宽	半径	动态载荷	静态载荷	脂润滑	油润滑	
	d	D	B	min			r/min	r/min	(kg)
mm	mm	mm							
62200	10	30	14	0.6	2.38	5.1	24000	30000	0.049
62201	12	32	14	0.6	3.05	6.82	22000	28000	0.053
62202	15	35	14	0.6	3.72	7.65	19000	24000	0.059
62203	17	40	16	1	4.78	9.58	17000	20000	0.091
62204	20	47	18	1	6.65	12.8	15000	18000	0.131
62205	25	52	18	1	7.88	14	12000	15000	0.148
62206	30	62	20	1.5	11.5	19.5	10000	13000	0.236
62207	35	72	23	1.5	15.2	25.5	9000	11000	0.375
62208	40	80	23	2	18.6	18.2	8000	10000	0.406
62301	12	37	17	1	5.08	9.72	20000	26000	0.095
62302	15	42	17	1	5.42	11.5	19000	24000	0.113
62303	17	47	19	1	6.58	13.5	17000	20000	0.141
62304	20	52	21	1.5	7.88	15.8	16000	18000	0.197
62305	25	62	24	1.5	11.5	22.2	13000	16000	0.317
62306	30	72	27	2	15.2	27	11000	14000	0.473
62307	35	80	31	2	19.2	33.2	9000	11000	0.658
16001	21	28	7	0.3	5.08	2.38	27000	32000	0.024
16002	15	32	8	0.3	5.6	2.55	23000	28000	0.025
16003	17	35	8	0.3	6.82	3.38	21000	25000	0.032
16004	20	42	8	0.3	7.9	4.5	17000	21000	0.052
16005	25	47	8	0.3	8.8	5.6	15000	18000	0.059
16006	30	55	9	0.3	11.2	7.4	13000	15000	0.084
16007	35	62	9	0.3	12.2	8.8	11000	13000	0.107
16008	40	68	9	0.3	12.6	9.6	9800	12000	0.125
16009	45	75	10	0.6	15.6	12.2	8900	10000	0.155
16010	50	80	10	0.6	16.1	13.1	8200	9700	0.166
16011	55	90	11	0.6	19.4	16.2	7400	8800	0.207
16012	60	95	11	0.6	19.9	17.5	6900	8100	0.224
16013	65	100	11	0.6	20.5	18.6	6600	7800	0.241
16014	70	100	13	0.6	27.9	25	5700	7200	0.386