

型号	主要尺寸							额定载荷		最大转速		重量
Bearing No.	Main Dimension(mm)							Load Rating(KN)		Max Runout Speed		Weight
	Bore 内径		Outer Diameter外径		Width宽		Radius(r) 半径	Dynamic 动态载荷	Static 静态载荷	Grease脂	Oil油	
	d		D		B		min			r/min	r/min	
	mm	inch	mm	inch	mm	inch		r/min	r/min			
685	5	0.1969	11	0.4331	3	0.1181	0.15	0.83	0.39	36000	45000	0.001
686	6	0.2362	11	0.5118	3.5	0.1378	0.15	0.901	0.441	34000	43000	0.002
687	7	0.2756	13	0.5512	3.5	0.1378	0.15	1.029	0.539	32000	40000	0.002
688	8	0.315	14	0.6299	4	0.1575	0.2	1.078	0.588	30000	38000	0.003
689	9	0.3543	16	0.6693	4	0.1575	0.2	1.319	0.694	28000	36000	0.003
6800	10	0.3937	19	0.748	5	0.1969	0.3	-	-	26000	34000	0.005
6800W7	10	0.3937	19	0.748	7	0.2756	0.3	1.473	0.833	26000	34000	0.005
6801	12	0.4724	21	0.8268	5	0.1969	0.3	1.549	0.922	22000	30000	0.006
6802	15	0.5906	24	0.9449	5	0.1969	0.3	1.639	1.041	20000	28000	0.007
6803	17	0.6693	26	1.0236	5	0.1969	0.3	2.646	1.715	19000	26000	0.008
6804	20	0.7874	32	1.2598	7	0.2756	0.3	2.84	1.96	17000	22000	0.018
6805	25	0.9843	37	1.4567	7	0.2756	0.3	3.087	2.352	15000	19000	0.022
6806	30	1.1811	42	1.6535	7	0.2756	0.3	4.9	4	12000	16000	0.026
6807	35	1.378	47	2.0472	7	0.2756	0.3	5.1	4.4	11000	15000	0.03
6808	40	1.5748	52	2.2835	7	0.2756	0.3	6.2	5.4	10000	13000	0.033
6809	45	1.7717	58	2.5591	7	0.2756	0.3	6.6	6.1	8000	11000	0.04
6810	50	1.9685	65	0.4331	7	0.2756	0.3	-	-	6000	9000	0.052
694	4	0.1575	11	0.5118	4	0.1575	0.15	0.72	0.39	38000	47000	0.0018
695	5	0.1969	13	0.5906	4	0.1575	0.2	1.12	0.59	34000	43000	0.002
696	6	0.2362	15	0.6693	5	0.1969	0.2	1.568	0.784	32000	40000	0.004
697	7	0.2756	17	0.748	5	0.1969	0.3	1.72	0.864	30000	38000	0.005
698	8	0.315	19	0.7874	6	0.2362	0.3	1.325	0.694	28000	36000	0.007
699	9	0.3545	20	0.8661	6	0.2362	0.3	2.54	1.37	27000	34000	0.008
6900	10	0.3937	22	0.9449	6	0.2362	0.3	2.221	1.235	25000	32000	0.009

6901	12	0.4724	24	1.1024	6	0.2362	0.3	2.639	1.501	22000	28000	0.011
6902	15	0.5906	28	1.1811	7	0.2756	0.3	2.79	1.65	20000	26000	0.016
6903	17	0.6693	30	1.4567	7	0.2756	0.3	5.03	3.063	18000	24000	0.018
6904	20	0.7874	37	1.6535	9	0.3543	0.3	5.63	3.68	17000	22000	0.036
6905	25	0.9843	42	1.8504	9	0.3543	0.3	5.82	3.97	14000	18000	0.042
6906	30	1.1811	47	2.1654	9	0.3543	0.3	9.5	6.8	13000	16000	0.048
6907	35	1.378	55							12000	15000	0.074
6908	40	1.5748	62	2.4409	12	0.4724	0.6	13.7	9.900 -	11000	13000	0.11
6909	45	1.7717	68	2.6772	12	0.4724	0.6	14.1	10.900 -	9000	11000	0.132
6910	50	1.9685	72	2.8346	12	0.4724	0.6	14.5	11.700 -	5000	9000	0.133