

轴承型号	主要尺寸							极限转速		额定载荷		重量
Bearing No.	Main Dimension(mm)							Limited rotate speed		Rating Load		Weight
	d	D	T	B	C	R	r	Grease 脂润滑	Oil 油润滑	Dynamic Cr动	Static Cor静	(kg)
LM11749/10	17.462	39.878	13.843	14.605	10.668	1.3	1.3	10000	13000	23.4	23	0.081
▲	19.05	45.237	15.494	16.637	12.065	1.3	1.3	9000	12000	29.9	30.5	0.125
L4S44d/10	29	50.292	14.224	14.732	10.668	3.5	1.3	7000	9000	27.7	36.2	0.11
▲	34.925	65.088	18.034	18.288	13.97	特殊	1.3	5600	7500	48.5	5.9	0.245
▲	21.43	50.005	17.526	18.288	13.97	1.3	1.3	8000	11000	37	37.5	0.169
▲ L44643/10	25.4	50.292	14.224	14.732	10.668	1.3	1.3	7300	10000	28.5	34	0.123
L44649/10	26.988	50.292	14.224	14.732	10.668	3.5	1.3	7300	10000	28.5	34	0.118
▲	31.75	59.131	15.875	16.764	11.811	特殊	1.3	6000	8500	36.5	43.5	0.182
■	31.75	59.131	16.637	16.764	11.8	4	1.8	6000	8500	36	43	0.187
■	31.75	59.131	15.875	16.764	15.8	4	1.8	6000	8500	36	43	0.19
LM67049/10	31.75	59.131	15.875	16.7	12	4	1.7	6000	8500	36	43	0.182
HM88649/10	30.162	64.292	21.433	21.433	16.67	1.5	1.5	6000	8000	55	72.5	0.335
28985A/20	60.325	101.6	25.4	25.4	19.845	3.5	3.3	3700	4500	98.2	149	0.79
28584/21	52.388	92.075	24.608	25.4	19.845	3.5	0.8	4100	5200	91.6	130	0.66
29590/22	66.676	107.95	25.4	25.4	19.05	3.5	3.3	3300	4200	102	158	0.64
L68149/11	34.988	59.974	15.875	16.764	11.938	特殊	1.3	6100	7000	35.5	49.3	0.18
▲ L6B149/10	35	59.131	15.875	16.764	11.938	特殊	1.3	6000	8000	34	46	0.165
JL 26749/10	31.87	53	14.5	15	11.5	3	1.5	6900	8800	40	60	0.13
JL69349/10	38	63	17	17	13.5	特殊	1.3	5700	7200	39.8	55	0.19
JL69345E/10	38	63	17	19	13.5	特殊	1.3	5700	7200	39.8	55	0.21
LM102949/10	45.242	73.431	19.558	19.812	15.748	3.5	0.8	4700	6400	55.5	78	0.308
LM29748/10	38.1	65.088	18.034	18.286	13.97	特殊	1.3	5500	7100	45	60.3	0.22

JLM104946/1	50	82	21.5	21.5	17	3	0.5	4400	5500	75.2	104	0.41
LM501349/10	41.275	73.431	19.588	19.812	14.732	3.5	0.8	4900	6700	55.5	69	0.328
L521949/10	107.95	146.05	21.433	21.433	16.67	1.5	1.5	2200	3000	93.5	155	0.965
15123/15245	31.75	62	18.161	19.05	17	特殊	1.3	6000	8000	43.5	51.5	0.235
0238/9720E	50.5	90	20.75	20	14.732	1.5	特殊	4200	5400	53.5	66	0.347
31594/31520	34.925	76.2	29.37	28.575	16.67	1.5	3.3	5200	6600	82.7	107	0.62
2788/2720	38.1	76.2	23.812	25.654	19.05	3.5	3.3	5000	6700	68	81	0.495
2580/2520	31.75	66.421	25.4	25.357	20.638	8	3.3	6100	7500	77.5	94.4	0.39
25580/20	44.45	82.931	23.812	25.4	1.905	3.5	0.8	4500	6000	78.5	98	0.555
639297	28000	57.150	17.462	17.5	13.5	2.3	1.5	6600	8300	41	59	0.205
639154	25.995	57.15	17.462	17.5	13.5	2.3	1.5	6900	8800	42	59	0,22
439373	35	59.975	15.975	18.455	11.906	2	1.5	6800	8600	39	50	0.183
442327N	22	41	14.4	14.5	11.4	0.8	0.6	8800	11000	35	47	0.08
09081/09196	20.625	49.225	19.845	21.539	17.462	1.5	1.3	8000	10000	39.7	40.5	0.17
LM300849/11	40.988	67.975	17	18	13.5	特殊	1.5	5400	6800	46.1	\$35	0,23
HM803146/1	41.275	88.900	30.162	29.37	23.02	3.5	3.3	4600	5700	105	114	0.69
HM603146/1 1	41.275	88.9	30.162	29.37	23.02	3.5	0.8	4600	5700	105	114	0.9
537/532X	50.8	107.95	36.512	36.957	28.57	3.6	3.2	3600	5100	136	172	0.1
365/362A	50	86.9	20.638	22.225	16.513	2	1.2	4400	5800	74,3	87.3	0.128
• IKOS020	20	42	特殊	17	16.5	1	特殊	9000	11000	2.45	28	0.16
• IKOS025	25	47	特殊	17	16.5	1	特殊	8000	10000	28.5	34	0.24
• IKOS030	30	55	特殊	19	18.5	1.5	特殊	6600	8400	39	47.5	0.29
• IKOS035	35	62	特殊	20	19.5	1.5	特殊	6000	7500	39	50	0.383
• IKOS040	40	68	特殊	21	20.5	1.5	特殊	5400	7000	54	71	0.403
• IKOS045	45	75	特殊	22	21.5	1.5	特殊	4900	6200	60	83	0.66
• IKOS050	50	60	特殊	22	21.5	1	特殊	■	■	■	■	
• IKOS060	55	95	特殊	26	25	1.5	特殊	■	•	•	•	
IKOS070	70	110	特殊	27	26.5	1.5	特殊	3300	4400	103	158	0.95

IKOS080	80.000	128	特殊	30	29.5	1.5	特殊	2800	3800	166	256	1.35
IKOS090	90	140	特殊	33.500	33	2	特殊	2500	3400	194	291	1.85
IKOS100	100	150	特殊	33.500	33	2	特殊	2300	3100	204	328	2,10
IKOS100	110.00	160	特殊	40	39.5	3	特殊	2300	2900	240	300	3.3
IKOS120	120.00	170	特殊	40	39.5	3	特殊	2100	2600	250	420	3.5
TRB1154/32	36.513	60	29.37	26.4	23.813	1.5	i.i	5000	6300	78	65	0.6
33209R	45	85	32	32	25	1.5	1.5	4600	6200	112	149	0.818
14138A/14276	34.925	69.102	19.845	19.583	15.875	3.5	1.3	5700	7600	52.9	56.2	0.344
469/456X	57.15	107.775	30.162	29.317	24.605	2.3	3.3	3700	4900	126	165	■
3490/20	38.1	79.375	29.37	29.771	23.812	3.5	3.3	5200	6900	87.4	105	■
18590/20	41.275	73.025	16.667	17.462	12.7	3.5	1.5	5200	6900	45.9	55.6	■
29586/20	63.5	107.95	25.4	25.4	19.05	1.5	3.3	3400	4500	92.8	143	■
HM218248/10	89.974	146.975	40	40	32.5	7	3	2500	3300	20.6	310	■
HM518445/10	88.9	152.4	39.688	39.6	30.2	6.4	3.2	2400	3200	240	359	■
LM12749/11	21.986	45.974	15.494	16.637	12.065	1.3	1.3	8900	12000	30.1	34.6	■
LM13600LA/10	38.1	69.012	19.812	19.05	15.083	3.5	2.3	5600	7500	49.2	62	■
M88048/10	33.338	66.262	22.225	22.225	17.462	0.8	1.6	6000	7900	56.1	71.1	■
33895/21	53.975	95.25	27.783	26.575	22.225	1.6	0.8	4100	5400	ioe	141	■
33889/21	50.8	95.25	27.783	28.575	22.225	3,6	0.8	4100	5400	108	141	■
33885/21	44.45	95.25	27.783	28.575	22.225	0.8	2.4	4100	5400	108	141	■
HM212049/10	66.675	122.238	38.1	38.354	29.718	3.5	1.5	3200	4300	191	249	■
387A/382A	57.15	96.838	21	21.946	15.875	3.6	0.8	3900	5200	80.4	101	
Tr070904	50	83	20.5	20.5	15.5	1	1	4600	6100	36	56.3	0.389
CBK257	15	42	13	13.5	10	1	1	10000	1400	21.9	19.2	0.098
JM515649/10	80	130	35	34	28.5	3	2.5	2600	3800	166	256	0.85
JM178149A/10	90	145	35	15	27	3	2.5	2500	3400	194	291	0.74
T509024	50	90	24.3	20	19.5	1.5	1.5	4300	5700	84.5	113	0.675
L21549/11	15.875	34.988	10.998	31.56	8.712	1.2	1.2	12000	16000	14.5	14.3	
TIE174595	45	95	36	35	30	2.5	2.5	4300	5700	140	177	1.2

JRM3939/396 8XD	39	68	■	18.5	37	3.5	1	4000	5200	63,5	95	0.54
JRM3939/397 2XD	39	72	■	18.5	37	3.5	1.1	3900	5000	63	94	0.665
JRM363e/387 0XD	38	70	■	19	38	3.5	1	4000	5100	63	94	0.63
JRM4040/407 2XD	40	72	■	18.5	37	3.5	1.1	3800	4200	63	94	0.636
JRM2525/255 2XD	25	52	■	18.5	37	3.5	0.8	5500	7000	48	69	0.37
JRM2828/285 8XD	28	58	■	21	42	2.3	1	4800	6500	57	72	0.5
JRM4242/428 2XO	42	62	■	18	36	2.5	0.7	3400	4100	81	110	0.84
350210X2	50	■	49	20	39	2.5	0.7	2800	3000	92	117	1.15
A-48674	42	76	■	19.5	39	3.5	0.8	3400	3600	95	121	0.73
E-21003203	30	60.03	■	18.5	37	2.5	1	4600	6000	52	76	0.41
E-21003212	35	65		17.5	35	2	0.7	4200	5600	68.2	95.7	0.5
E-21003213	49	84	■	24	48	3	0.7	3200	4200	111	193	1.05
E-21003325	55	90	■	30	60	3.5	0.8	3000	3800	151	232	1.2
CRI-0569	27	52	■	22.5	43	2	1	5300	6700	41	67	0.423
▲ 331335/820	35	■	35	16.4	39.5	2		3400	3600	63	91	0.93