

型号	内径		尺寸								额定载荷		重量(kg)
Unit No.	Shaft Dia		Dimensions(mm)								Rating Load		Mass(kg)
	d		D	B	C	S	S1	G	h	ds	动态额定负 荷	静态额定负 荷	
	in	mm									Dynamic Cr	Static Cor	
UC305-14	7/8												0.38
305-15	15/16		62	38	21	15	23	6	6.2	M6X1	22360	11500	0.36
305		25	2.4409	1.4961	0.8268	0.5906	0.9055	0.2362	0.2441	1/4-28UNF			0.35
305-16	1												0.34
UC306-18	1-1/8		72	43	24	17	26	6	6.5	M6X1	27000	15200	0.58
306		30	2.8346	1.6929	0.9449	0.6693	1.0236	0.2362	0.2559	1/4-24UNF			0.56
306-19	1-3/16												0.56
UC307-20	1-1/4		80	48	25	19	29	8	7.2	M8X1	33500	19200	0.77
307-21	1-5/16		3.1496	1.8898	0.9843	0.748	1.1417	0.315	0.2835	5/16-			0.74
307-22	1-3/8												0.71
307		35											0.71
UC308-24	1-1/2		90	52	28	19	33	10	8.5	M10X1.25	40560	24000	1
308-25	1-9/16		3.5433	2.0472	1.1024	0.748	1.2992	0.3937	0.3346	3/8-24UNF			0.98
308		40											0.96
UC309-26	1-5/8		100	57	30	22	35	10	9	M10X1.25	53000	31800	1.36
309-27	1-11/16		3.937	2.2441	1.1811	0.8661	1.378	0.3937	0.3543	3/8-24UNF			1.33
309-28	1-3/4		110	61	32	22	39	12	9.9	M12X1.25			1.3
309		45	4.3307	2.4016	1.2598	0.8661	1.5354	0.4724	0.3898	7/16- 20UNF			1.28
UC310-30	1-7/8	50									61750	37800	1.74
310-31	1-15/16												1.68
310													1.65
UC311-32	2	55	120	66	34	25	41	12	10.6	M12X1.25	71500	44800	2.08
311-34	2-1/8		4.7244	2.5984	1.3386	0.9843	1.6142	0.4724	0.4173	7/16- 20UNF			1.9

311													1.9
311-35	2-3/16												1.87
UC312-36	2-1/4		130	71	36	26	45	12	11.3	M12X1.25	81600	51800	2.65
312		60	5.1181	2.7953	1.4173	1.0236	1.7717	0.4724	0.4449	7/16-20UNF			2.60
312-38	2-3/8												2.57
312-39	2-7/16												2.5
UC313-40	2-1/2		140	75	38	30	45	12	12.1	M12X1.25	93860	60500	3.30
313		65	5.5118	2.9528	1.4961	1.1811	1.7717	0.4724	0.4764	7/16-20UNF			3.25
UC314-44	2-3/4		150	78	40	31	47	12	12.8	M12X1.25	104260	68000	3.96
314		70	5.9055	3.0709	1.5748	1,2205	1.8504	0.4724	0.5039	7/16-20UNF			3.95
UC315		75	160	82	42	32	50	14	13.5	M14X1.5	113360	76800	4.33
315-48	3		6.2992	3.2283	1.6535	1.2598	1.9685	0.5512	0.5315	1/2-20UNF			4.24
UC316		80	170	86	44	34	52	14	14.5	M14X1.5	122850	96500	5.57
			6.6929	3.3858	1.7323	1.3386	2.0472	0.5512	0.5709	1/2-20UNF			
UC317-52	3-1/4	85	180	96	46	40	56	16	15.5	M16X1.5	132600	96500	7.08
317			7.0866	3.7795	1.711	1.5748	2.2047	0.6299	0.6102	5/8-18UNF			6.84
UC318-56	3-1/2	90	190	96	48	40	56	16	16.5	M16X1.5	143000	108000	8.03
318			7.4803	3.7795	1.8898	1.5748	2.2047	0.6299	0.6496	5/8-18UNF			7.87
UC319		95	200	103	50	41	62	18	18	M16X1.5	156000	12000	8.91
319-50	3-3/4	7.87740 4.0551			1.9685	1.6142	2.4409	0.7087	0.7087	5/8-18UNF			8.88
UC320		100	215	108	54	42	66	18	19	M16X1.5	171600	140000	11.2
320-64	4		8.4646	4.252	2.216	1.6535	2.5984	0.7087	0.748	5/8-18UNF			11