

型号	内径		尺寸							额定载荷		重量(kg)
Unit No.	Shaft Dia		Dimensions(mm)							Basic Rating Load N		Mass(kg)
	d		D	C	h	B	S	G	d1	Dynamic Cr	Static Cor	
	in	mm										
SB201		12										0.09
201-8	1/2		40	12	3.6	22	6	4	M5X0.8			0.09
202		15	1.5748	0.4724	0.1417	0.8661	0.2362	0.1575	10#-32UNF	9550	4780	0.08
202-10	5/8											0.1
203		17										0.1
203-11	11/16											0.15
SB204-12	3/4		47	14	4	25	7	5	M6X1	12800	6650	0.15
204		20	1.8504	0.5512	0.1575	0.9843	0.2756	0.1969	1/4-28UNF			0.18
SB205-14	7/8		52	15	4.3	27	7.5	5.5	M6X1	14000	7880	0.18
205-15	15/16		2.0472	0.5906	0.1693	1.0630	0.2953	0.2165	1/4-28UNF			0.17
205		25										0.16
205-16	1											0.28
SB206-18	1-1/8		62	16	5	29	8	6	M6X1	19500	1120	0.27
206		30	2.4409	0.6299	0.1969	1.1417	0.3150	0.2362	1/4-28UNF			0.26
206-19	1-3/16											0.25
206-20	1-1/4											0.24
SB207-20	1-1/4		72	18	5.7	32	9	6	M6X1	25700	15200	0.46
207-21	1-5/16		2.8346	0.7087	0.2244	0.2598	0.3543	0.2362	1/4-28UNF			0.42
207-22	1-3/8											0.41
207		35										0.38
207-23	1-7/16											0.37
SB208-24	1-1/2		80	19	6.2	34	9.5	7	M8X1	29600	18200	0.6
208-25	1-9/16		3.1496	0.7480	0.2441	0.3386	0.3740	0.2756	5/16-24UNF			0.58

