

Bearing No.	d	D	B	C	d1≈	dk≈	rsmin	r1min	α/(°)≈
GE30ES-2RS	30	47	22	18	34	40	0.6	0.6	6
GE35DS	35	55	25	20	39	47	0.6	1	6
GE35ES	35	55	25	20	39	47	0.6	1	6
GE35ES-2RS	35	55	25	20	39	47	0.6	X	6
GE40DS	40	62	28	22	45	53	0.6	1	7
GE40ES	40	62	28	22	45	53	0.6	1	7
GE40ES-2RS	40	62	28	22	45	53	0.6	1	7
GE45DS	45	68	32	25	50	60	0.6	1	7
GE45ES	45	68	32	25	50	60	0.6	1	7
GE45ES-2RS	45	68	32	25	50	60	0.6	1	7
GE50DS	50	75	35	28	55	66	0.6	1	6
GE50ES	50	75	35	28	55	66	0.6	1	6
GE50ES-2RS	50	75	35	28	55	66	0.6	1	6
GE55DS	55	85	40	32	62	74	0.6	1	7
GE55ES	55	85	40	32	62	74	0.6	1	7
GE55ES-2RS	55	85	40	32	62	74	0.6	1	7
GE60DS	60	90	44	36	66	80	1	1	6